

# **HACKNET : SPICE Netlist Generator**

---

A netlist generator manual

**David Fang**

---

This manual describes the usage and operation of HACKT's `hacknet` spice netlist generator.

This document can also be found online at <http://www.csl.cornell.edu/~fang/hackt/hacknet>. ■

The main project home page is <http://www.csl.cornell.edu/~fang/hackt/>.

Copyright © 2009 Cornell University

Published by ...

Permission is hereby granted to ...

## Short Contents

1	Introduction . . . . .	1
2	Usage . . . . .	3
	Concept Index . . . . .	5



## Table of Contents

<b>1</b>	<b>Introduction</b> .....	<b>1</b>
<b>2</b>	<b>Usage</b> .....	<b>3</b>
2.1	Option Summary .....	3
2.2	Configuration Options .....	3
	<b>Concept Index</b> .....	<b>5</b>



# 1 Introduction

`hacknet` is a SPICE netlist generator for the HACKT suite. The input is a HAC file containing production rules, usually connected through instance hierarchy. The output is a hierarchical netlist with devices, subcircuits, and instances. The output should be suitable for SPICE-like circuit simulators.

How it works...



## 2 Usage

This chapter describes `hacknet`'s command-line options, and configuration file options.

Usage: `hacknet [options] obj-file`

The resulting netlist is printed to `standard-out`, so it is common practice to redirect it to a file. Diagnostic messages will appear in `standard-error`.

### 2.1 Option Summary

For options that take an argument, the space between the flag and the argument is optional.

`-c file` [User Option]

Parse configuration options from *file*. Options are of the form `key=values` with no space characters separating the `=`. Values may be singleton, comma-separated, or omitted. The same options can also be passed in through the command-line via `-f`. This option is repeatable and cumulative. See [Section 2.2 \[Configuration Options\]](#), page 3.

`-f options...` [User Option]

Parse configuration options from *options*. Options are of the same key-value format as in the configuration file, see option `-c`. Options are space-separated instead of newline-separated. This option is repeatable and cumulative. See [Section 2.2 \[Configuration Options\]](#), page 3.

`-h` [User Option]

Help. Print usage and exit.

`-H` [User Option]

Describe all configuration options. See [Section 2.2 \[Configuration Options\]](#), page 3. See also the installed documentation for `hacknet.info,html,pdf`.

`-t type` [User Option]

Instead of using the top-level instances in the source file, instantiate one instance of the named *type*, propagating its ports as top-level globals. In other words, use the referenced type as the top-level scope, ignoring the source's top-level instances. Convenient takes place of copy-propagating a single instance's ports.

### 2.2 Configuration Options

There are two ways to pass configuration options to `hacknet`. One is through the `-f` option on the command-line, the other way is to pass them in through a configuration file with the `-c` option. The option value specifications share the same syntax: `key=values` where *values* can be blank, a single value, or a comma-separated list of values. A key-value specifier is not permitted to have spaces in the string!

In a configuration file, blank lines are ignored, as well as lines that begin with `#` (pound).

`lambda` [User Option]

Technology-dependent scaling factor for device lengths and widths, the multiplier factor applied to lengths and widths specified in PRS. Default: 1.0

- length\_unit** [User Option]  
Suffix-string to append to emitted length and width parameters. Can be a unit such as "u" or "n", or exponent such as "e-6" or "e-9". Default: u (micron)
- std\_n\_width** [User Option]  
Default width (in lambda) for NFETs used in logic, where unspecified.
- std\_p\_width** [User Option]  
Default width (in lambda) for PFETs used in logic, where unspecified.
- std\_n\_length** [User Option]  
Default length (in lambda) for NFETs used in logic, where unspecified.
- std\_p\_length** [User Option]  
Default length (in lambda) for PFETs used in logic, where unspecified.
- stat\_n\_width** [User Option]  
Default width (in lambda) for NFETs used in keepers (staticizers), where unspecified.
- stat\_p\_width** [User Option]  
Default width (in lambda) for PFETs used in keepers (staticizers), where unspecified.
- stat\_n\_length** [User Option]  
Default length (in lambda) for NFETs used in keepers (staticizers), where unspecified.
- stat\_p\_length** [User Option]  
Default length (in lambda) for PFETs used in keepers (staticizers), where unspecified.
- nested\_subcircuits** [User Option]  
If this option is set to 1, then emit local subcircuits as nested definitions within their used definitions. Not sure which variants of SPICE support this. Default: 0
- emit\_top** [User Option]  
If set to 1, include the top-level instances in the netlist output. Setting this to 0 is useful for producing a library of subcircuit definitions for every type that was instantiated, recursively w.r.t dependencies. Default: 1

# Concept Index

## C

command-line .....	3
configuration .....	3

## F

flags .....	3
-------------	---

## I

introduction .....	1
--------------------	---

## O

options .....	3
---------------	---

## U

usage .....	3
-------------	---

